CEDAR CITY COURT 2005 MISCELLANEOUS REMODELING

100 EAST CENTER STREET CEDAR CITY, UTAH 84501



STATE OF UTAH
DEPARTMENT OF ADMINISTRATIVE SERVICES
DIVISION OF FACILITIES CONSTRUCTION AND MANAGEMENT
4110 State Office Building / SLC, Utah 84114 / (801) 538-3018

DFCM PROJECT NO. 05017150

SCOTT P. EVANS - ARCHITECT AND ASSOCIATES P.C.

ARCHITECT 108 WEST CENTER STREET (801) 298-1368 BOUNTIFUL, UTAH

BHB CONSULTING


STRUCTURAL ENGINEER 244 WEST 300 NORTH #202 (801) 355-5656 SALT LAKE CITY, UTAH VAN BOERUM & FRANK ASSOCIATES


MECHANICAL ENGINEER
330 SOUTH 300 EAST


(801) 530-3148 SALT LAKE CITY, UTAH

KEY ENGINEERING, INC.


ELECTRICAL ENGINEER 7231 SOUTH 900 EAST (801) 307-0115 MIDVALE, UTAH









SHT. NO.	DRAWING TITLE				
GI-001	TITLE SHEET				
GI-002 GENERAL INFORMATION					
SJ001	GENERAL STRUCTURAL NOTES				
SB101	PARTIAL STRUCTURAL PLANS				
SB501	STRUCTURAL DETAILS				
SB601	SCHEDULES				
AD-101	DEMOLITION PLANS & KEYED NOTES				
AE-101	FLOOR PLANS & KEYED NOTES				
AE-102	REFLECTED CEILING PLANS & KEYED NOTES				
AE-201	INTERIOR ELEVATION & KEYED NOTES				
AE-301	SECTIONS				
AE-501	DETAILS				
AE-502	DETAILS				
AE-503	DETAILS				
AE-601	SCHEDULES				
ME-000	LEGEND				
MD-101	MECHANICAL DEMOLITION PLANS				
ME-101	MECHANICAL PLANS				
ME-401	DETAILS				
PD-101	-101 PLUMBING DEMOLITION PLANS				
PE-101	PLUMBING PLANS				





0 REMODELING 0 MS 200





COPYRIGHT: SCOTT P. EVANS ARCHITECT - 2005 SHEET TITLE **GENERAL INFORMATION**

3/28/05 CONSTRUCTION DOCUMENT

MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150

ARCH. PROJECT NO: 04-47

DRAWN BY: JBE

CHECKED BY: SPE

DESIGNED BY: SPE

CAD DWG FILE: GI-002.DWG

GI-002

GENERAL STRUCTURAL NOTES

GENERAL

- 1. The structural notes are intended to complement the project specifications. Specific notes and details in the drawings shall govern over the structural notes and typical details. 2. Typical details and sections shall apply where specific details are not shown.
- 3. The contractor shall verify all site conditions and dimensions. If actual conditions differ from those shown in the contract drawings, the contractor shall immediately notify the architect/engineer before proceeding with the fabrication or construction of any effected elements. 4. Omissions or conflicts between the contract drawings and/or specifications shall be brought to the attention of the architect/engineer before proceeding with any work involved. In case of conflict,

follow the most stringent requirement as directed by the architect/engineer at no additional cost to

- the owner. 5. The contractor shall submit a written request to the architect/engineer before proceeding with any changes, substitutions or modifications. Any work done by the contractor before receiving written approval will be at the contractor's risk.
- 6. The contractor shall coordinate with all trades any items that are to be integrated into the structural system such as openings, penetrations, mechanical and electrical equipment, etc. Sizes and locations of mechanical and other equipment that differs from those shown on the contract drawings shall be reported to the architect/engineer.
- 7. The contractor shall provide adequate shoring and bracing as required for his method of erection. Shoring and bracing shall remain in place until final connections for the permanent members are completed. The building shall not be considered stable until all connections are completed. Walls shall not be considered self-supporting and shall be braced until the roof system is
- 8. Site observations by BHB Consulting Engineers, P.C.'s field representative shall not be construed as approval of construction procedures nor special inspection.
- 9. Detailing and shop drawing production for structural elements will require information (including dimensions) contained in the architectural, structural and/or other consultants' drawings. The structural drawings shall be used in conjunction with the architectural and other consultant's drawings. Some dimensions and elements such as elevations, depressions, slopes, mechanical housekeeping pads, etc. are not shown in the structural drawings. All dimensions shown on structural drawings shall be verified by contractor with architectural, mechanical and electrical
- 10. Review of shop drawing submittals by BHB Consulting Engineers, P.C. is for general compliance only and is not intended for approval. The shop drawing review shall not relieve the contractor from the responsibility of completing the project according to the contract documents.
- 11. Shop drawings made from reproductions of the contract drawings will be rejected unless the contractor signs a release agreement prior to the shop drawings being reviewed.
- 12. Only an authorized representative of BHB Consulting Engineers, P.C. may make changes to these contract drawings. BHB Consulting Engineers, P.C. shall not be held responsible or liable for any claims arising directly or indirectly from changes made without written authorization by an authorized representative of BHB Consulting Engineers, P.C.

BASIS OF DESIGN

- Governing Building Code International Building Code 2003
- Roof Snow Load
- a. Ground Snow Load $P_a = 43 \text{ psf}$ b. Snow Importance Factor $I_{s} = 1.0$ c. Snow Exposure Coefficient $C_e = 1.0$
- d. Thermal Exposure Coefficient $C_t = 1.0$ d. Roof Snow Load $P_f = 0.7 C_e C_t I_s P_g = 30 psf plus Snow Drift$

FOUNDATION

- Soils Report by Kleinfelder,
- Dated June 6, 1990. 2. Soil Bearing Pressure: 1500 psf, on Compacted Fill.

EARTHWORK

1. Consult the project specifications and soils report for further earthwork requirements.

CONCRETE

1.	Materials,	unless	noted	otherwise:

ASTM C 33 a. Normal weight aggregates

ASTM 615 Grade 60 (Fy = 60 ksi) b. Reinforcing Steel

Use Grade 40 (Fy = 40 ksi) for field bent dowels with spacings indicated reduced by 1/3.

ASTM F1554 Grade 36 with ASTM A563 heavy hex c. Anchor Rods nuts with hardened washers

d. Admixtures: Air-entraining admixtures comply with ASTM C 260 (when used).

Calcium chloride shall not be added to the concrete mix.

e. Type II cement complying with ASTM C-150 shall be used for all concrete.

f. The water/cement ratios shall meet the requirements of ACI 318.

g. Provide air entraining as recommended by ACI 318. h. No aluminum conduit or product containing aluminum or any other material injurious to concrete shall be embedded in concrete.

2. Compressive strengths of concrete at 28 days shall be as follows:

a. Footings. .3,000 psi b. Interior Slabs on Grade.. ..3,000 psi

3. Only one grade or type of concrete shall be poured on the site at any given time. 4. The contractor shall be responsible for the design, detailing, care, placement and removal of all

a. Supporting forms and shoring shall not be removed until structural members have acquired sufficient strength to safely support their own weight and any construction load to which they

may be subjected. In no case, however, shall forms and shoring be removed in less than 24 hours after concrete placement.

5. Reinforcement shall have the following concrete cover:

. Clear Cover Cast-in-place Concrete: a. Cast against and permanently exposed to earth. b. Formed concrete exposed to earth or weather:

#6 thru #18 bars. #5 and smaller bars.. c. Concrete not exposed to weather or in contact with ground: Slabs, Walls, Joists; #11 bars and smaller. Beams, Columns: Primary Reinf., Ties, Stirrups, Spirals......1-1/2"

Construction

a. Use chairs or other support devices recommended by the CRSI to support and tie reinforcement bars and WWF prior to placing concrete. WWF shall be continuously supported at 36" o.c. maximum. Reinforcing steel for slabs on grade shall be adequately supported on precast concrete units. Lifting the reinforcing off the grade during placement of

b. Concrete to be mechanically consolidated during placement per ACI standards. c. Contractor shall coordinate placement of all openings, curbs, dowels, sleeves, conduits, bolts,

inserts and other embedded items prior to concrete placement. d. All embeds and dowels shall be securely tied to formwork or to adjacent reinforcing prior to

the placement of concrete. e. No pipes, ducts, sleeves, etc shall be placed in structural concrete unless specifically detailed or approved by the structural engineer. Penetrations through walls when approved shall be built into the wall prior to concrete placement. Penetrations will not be allowed in footings or grade beams unless detailed. Piping shall be routed around these elements and footings stepped to avoid piping.

Reinforcing Bars shall not be welded unless specifically shown on drawings. In such cases, use only AWS standards. Do not substitute reinforcing bars for DBAs or HSAs.

a. At joints provide reinforcing dowels to match the member reinforcing, unless noted otherwise. b. At all discontinuous control or construction slab on grade joints, provide 2 - #4 x 48 inches.

EPOXY

- 1. Epoxy shall be "HIT RE 500" by Hilti Corporation, "Anchor-It" by Adhesive Technology Corporation, "Epcon Injection System" by Ramset/Redhead, "Power-Fast" by Rawl, or approved equal.
- 2. All drilled holes shall be 1/8 inch larger than the bar or anchor bolt being installed.
- 3. After drilling the proper size hole, clean the walls and bottom of the hole of all dust and debris using a nylon brush in conjunction with oil free compressed air. The hole shall be free of dust, debris and
- 4. Follow all manufacturer's recommendations for epoxy installation.

STRUCTURAL STEEL

Material:

ASTM A992 (50 ksi) a. Wide Flanges Section b. Other shapes & Plates ASTM A36 c. Steel Tubes ASTM A500 Grade B (46KSI) d. Deformed Bar Anchors (DBA) ASTM A496

ASTM A108 e. Headed Stud Anchors (HSA) f. Anchor Bolts

Gravity Columns ASTM F1554, Grade 36, with ASTM A563 heavy hex nuts and hardened washers Grade A

ASTM A325 g. Bolted Connections: 2. Fabrication and construction shall comply with the latest edition of the following Codes and Standards:

a. American Institute of Steel Construction (AISC), "Specification for the Design, Fabrication and Erection of Structural Steel for Buildings," with "Commentary".

b. AISC "Code of Standard Practice" excluding the following: Section 3.4, Section 4.4, Section

c. AISC "Specification for Structural Joints Using ASTM A325 or A490 Bolts"

d. American Welding Society (AWS), Structural Welding Code (specific items do not apply when they conflict with the AISC requirements).

e. AISC "Seismic Provision for Structural Steel Buildings" Welding

- a. All welding and cutting shall be performed by AWS certified welders.
- b. Use E-70 XX or as noted otherwise.
- c. All intersecting steel shapes which are not bolted shall be connected by a fillet weld all around, unless noted otherwise. Where fillet weld sizes are not shown they shall be 1/16" less than the thinnest of the connected parts for thicknesses 1/4" and larger. Fillet welds on plates less than 1/4" shall be of the same size as the thinnest of the connected part.
- d. Reinforcing Bars: Do not weld rebar except as specifically detailed in the drawings. In such cases, use only AWS standards.
- e. Do not weld anchor bolts, including "tack" welds.

4. Bolted Connections:

a. Use ASTM A325N bolts for steel to steel connections, as noted herein or as noted on the drawings. A325N bolts shall be used in connections for simple span framing and beam (or

- girder) to bearing plate connections. Tighten bolts to a snug tight condition. b. Use hardened washers beneath the turned element of all bolts or nuts. Use hardened beveled washers, to compensate for the lack of parallelism, where the outer face of the bolted parts has a slope greater than one in twenty with respect to the plane normal to the bolt axis. At oversized holes hardened washers or plates shall conform with ASTM F-436 and shall completely cover the slot after installation
- c. Where a steel to steel beam connection is not shown, provide a standard AISC framed connection for one half the total uniform load capacity of the beam for the span and steel specified.
- d. Bolts, nuts and washers shall not be reused.
- 5. Provide full-depth web-stiffener plates at each side of all beams at all bearing points. Stiffener plates shall be the thickness called out below unless noted otherwise and shall be welded both sides with fillet welds all around:

FLANGE WIDTH STIFFENER THICKNESS WELD SIZE

Less than 8 1/4"	1/4"	3/16"
8 1/4" to 12 1/4"	3/8"	1/4"
12 1/4" to 16 ½"	1/2"	5/16"
16 ½" to 20 ¾"	5/8"	3/8"

WOOD

1. Materials:

a. Framing Lumber shall be # 2 Douglas Fir-Larch or better unless noted otherwise.

b. Nails: Standard Common with the following properties: Shank Diameter Min. Penetration into Support Member 0.113" 1.25"

0.131" 1.50" 1.63" 0.148" 10d 1.63" 12d 0.148" 1.75" 0.162"

Fasteners other than common nails are not permitted without prior written approval from the

c. Bolts shall be ASTM A36 or equal with ASTM A563 heavy hex nuts and hardened washers, Grade A, unless noted otherwise.

2. All wood in contact with concrete, masonry or soil shall be pressure treated or be redwood.

3. General framing and carpentry shall be connected as per "Minimum Nailing Schedule" on sheet SB601 unless noted otherwise. 4. All framing anchors, post caps, hold downs, column bases, etc. shall be provided by Simpson

Strong-Tie or approved equal. 5. Provide solid shaped blocking at least 2 in.(nominal) thick and full depth of joist at ends and at each support of joist. Provide approved bridging at a 8'-0" o.c. maximum between joist end supports. Solid blocking between joists shall be nailed to the wood plate at the top of the wall with one Simpson "A35" framing anchor per each piece of blocking. Fill all holes in the framing anchors with 8-d x 1-1/2" nails (12 nails per A35).

SPECIAL INSPECTION AND QUALITY ASSURANCE

Special inspection and quality assurance, as required by section 1704 of the IBC, shall be provided by an independent agency employed by the owner unless waived by the building official. The contractor shall coordinate and cooperate with the required inspections. All testing and inspection reports shall be sent to the engineer for review. Items requiring special inspection and quality assurance are:

- 1. Soils (IBC 1704.7)
- 2. Concrete placement (IBC Section 1704.4)
- 3. Bolts installed in concrete (IBC Section 1704.4) 4. Concrete reinforcing steel placement (IBC Section 1704.4)
- 5. Structural welding, including steel deck (IBC 1704.3) 6. High Strength bolted connections (IBC Section 1704.3.3)
- 7. Epoxy Anchors (IBC Section 1704.13)

SCOTT P. EVANS **ARCHITECT** & ASSOCIATES P.C.

108 WEST CENTER STREET **BOUNTIFUL, UTAH 84010**

(801) 298-1368 (PHONE) (801) 298-2192 (FAX)

E-MAIL: spevans@qwest.net www.spe-architect.com

PROFESSIONAL SEAL

CONSULTANTS

STRUCTURAL ENGINEER BHB CONSULTING MECHANICAL ENGINEER VAN BOERUM & FRANK ASSOCIATES

ELECTRICAL ENGINEER

KEY ENGINEERING, INC

ED 0 0


 _		
0	3/28/05	CONST. DOCUMENTS
MARK	DATE	DESCRIPTION


OWNER PROJECT NO: 05017150 STRUCT. PROJECT NO: 05011 CAD DWG FILE: Q:\..05011 SJ001.DWC DRAWN BY: JM CHECKED BY: CH DESIGNED BY: JH A COPYRIGHT: SCOTT P. EVANS ARCHITECT - 2005

> SHEET TITLE GENERAL

> > STRUCTURAL NOTES

BHB Consulting Engineers Lake City, Utah 84103





ROOF FRAMING PLAN
PARTIAL PLAN 'B'

SCALE: 1/4"=1'-0"

O
4'
8'
16'

SECTION MARK
SHEET NUMBER
FOOTING DESIGNATION
TOP OF FOOTING ELEVATION

FSxx INDICATES SPOT FOOTING. SEE SCHEDULE
ON SHEET SB601.

SC-x INDICATES STEEL COLUMN. SEE SCHEDULE

ON SHEET SB601.

PLAN NOTES

ALL SPOT FOOTINGS SHALL BE CENTERED UNDER COLUMNS (UNO).
SEE ARCHITECTURAL DRAWINGS FOR DIMENSIONS TO ALL STEEL COLUMNS.
VERIFY ALL ROOF OPENINGS FOR MECHANICAL SHAFTS, DRAINS, ETC. WITH ARCHITECTURAL AND MECHANICAL DRAWINGS.
CONCTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS.



SCOTT P. EVANS
ARCHITECT
& ASSOCIATES P.C.

108 WEST CENTER STREET
BOUNTIFUL, UTAH 84010

(801) 298-2192 (FAX)

E-MAIL:
spevans@qwest.net

WEB:
www.spe-architect.com

(801) 298-1368 (PHONE)

PROFESSIONAL SEAL

CONSULTANTS

STRUCTURAL ENGINEER
BHB CONSULTING

MECHANICAL ENGINEER
VAN BOERUM & FRANK ASSOCIATES

ELECTRICAL ENGINEER
KEY ENGINEERING, INC.

COURT
ANEOUS
LING

CEDAR CITY COURT
2005 MISCELLANEOU
REMODELING
100 EAST CENTER STREET
CEDAR CITY, UTAH 84501

0 3/28/05 CONST. DOCUMENTS
MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150

STRUCT. PROJECT NO: 05011

CAD DWG FILE: Q:\..05011_SB101.DWG

DRAWN BY: JM

CHECKED BY: CH


DESIGNED BY: JH

A COPYRIGHT:
SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE

PARTIAL STRUCTURAL PLANS

SB101



SCOTT P. EVANS **ARCHITECT** & ASSOCIATES P.C

108 WEST CENTER STREET BOUNTIFUL, UTAH 84010 (801) 298-1368 (PHONE) (801) 298-2192 (FAX)

E-MAIL: spevans@qwest.net www.spe-architect.com

PROFESSIONAL SEAL

CONSULTANTS STRUCTURAL ENGINEER BHB CONSULTING MECHANICAL ENGINEER VAN BOERUM & FRANK ASSOCIATES **ELECTRICAL ENGINEER**

KEY ENGINEERING, INC

DE MISCELLANEC
REMODELING
100 EAST CENTER STREET
CEDAR CITY, UTAH 84501

3/28/05 CONST. DOCUMENTS MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150 STRUCT. PROJECT NO: 05011 CAD DWG FILE: Q:\..05011 SB501.DWG SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE STRUCTURAL DETAILS

SB501

CONCRETE FOOTING SCHEDULE												
MARK	WIDTH		DEPTH		REINFORCING CROSSWISE			F	REINFORG	ING LENGTH	WISE	COMMENTS
MANN	WIDTH	LENGTH	DEFIN	No.	SIZE	LENGTH	SPACING	No.	SIZE	LENGTH	SPACING	COMMENTS
FS4.5	4'-6"	4'-6"	12"	4	# 5	4'-0"	EQ	4	# 5	4'-0"	EQ	

CONCRETE FOOTING NOTES:

1. PLACE ALL FOOTING REINFORCING IN THE BOTTOM OF THE FOOTING WITH 3" CLEAR CONCRETE COVER (UNO). TOP REINFORCING, WHERE OCCURS, SHALL BE PLACED IN THE TOP OF THE FOOTING WITH 2" MINIMUM CONCRETE COVER.

IF FOOTINGS ARE EARTH-FORMED, FOOTINGS SHALL BE 6" LONGER AND WIDER THAN SCHEDULED. 4. SEE GENERAL STRUCTURAL NOTES FOR ADDITIONAL REQUIREMENTS.

5. SOME SCHEDULED FOOTINGS MAY NOT BE USED, SEE FOOTING AND FOUNDATION PLAN FOR FOOTING MARKS.

C1 CONCRETE FOOTING SCHEDULE

	STEEL COLUMN SCHEDULE						
MARK	SIZE	STEEL BASE PLATE	STEEL CAP PLATE	COMMENTS			
SC-1	HSS5x5x5/16	3/4" (SBP-1)	1/2" (SCP-1)				
SC-2	HSS4x4x3/16	3/4" (SBP-2)	1/2" (SCP-2)				

NO SCALE


STEEL COLUMN NOTES:

1. UNLESS NOTED OTHERWISE, ALL COLUMNS SHALL BE INSTALLED WITH (4) 3/4" ANCHOR BOLTS WITH 3" MINIMUM HOOKS. PROJECT ANCHOR BOLTS 3" MINIMUM ABOVE THE TOP OF THE BASE PLATE. EMBEDMENT SHALL BE 9" MINIMUM. ALL BOLTS SHALL BE INSTALLED WITH HARDENED WASHERS BENEATH THE NUT. ANY BOLT HOLES LARGER THAN THE BOLT DIAMETER PLUS 5/16" SHALL HAVE 5/16" PLATE WASHERS INSTALLED BENEATH THE HARDENED WASHERS.

ALL CAP PLATE BOLTS SHALL BE 3/4" A325N BOLTS, TYPICAL UNLESS NOTED OTHERWISE. ANCHOR BOLTS SHALL NOT BE WELDED (INCLUDING TACK WELDS).

SEE GENERAL STRUCTURAL NOTES FOR ADDITIONAL REQUIREMENTS. 5. SEE DETAIL C1/SB501 FOR COLUMNS EMBEDDED IN EXISTING MASONRY WALLS.

STEEL BASE PLATE TYPES: BASE PLATE LEGEND co = 1/2" MINIMUM ed = 1/2" MINIMUM bc = 3" MINIMUM0 0 BASE PLATE SBP-1 BASE PLATE SBP-2





8d OR 10d * NAILS SPACED AT 6" O.C. AT EDGES, 12" O.C. AT INTERMEDIATE SUPPORTS (EXCEPT WHERE SPANS ARE 48" OR MORE, THEN SPACE AT 6" O.C. AT SUPPORTS). FOR NAILING OF DIAPHRAGMS AND SHEAR WALLS, REFER TO SHEARWALL SCHEDULE.

MINIMUM NAILING NOTES:

1. NAILING SCHEDULE IS PER TABLE 2304.9.1 OF THE I.B.C. 2003. 2. NAILING REQUIREMENTS SHOWN HERE DO NOT REPLACE HARDWARE SHOWN ON THE PLANS OR DETAILS.

3. ALL NAILS USED ARE COMMON NAILS. 4. SEE GENERAL STRUCTURAL NOTES FOR ADDITIONAL REQUIREMENTS.

COUR CEDAR 2005

3/28/05 CONST. DOCUMENTS DATE DESCRIPTION

OWNER PROJECT NO: 05017150 STRUCT. PROJECT NO: 05011 CAD DWG FILE: Q:\..05011_SB601.DW DRAWN BY: JM CHECKED BY: CH DESIGNED BY: JH

"Engineering Results"

BHB Consulting Engineers
A Professional Corporation

244 West 300 North
Suite 202
Salt Lake City, Utah 84103
Phone: 801.355.5656
Fax: 801.355.5950
Email: bhb@bhbbengineers.com

SB601

PROFESSIONAL SEAL

SCOTT P. EVANS

ARCHITECT & ASSOCIATES P.C.

D 108 WEST CENTER STREET

BOUNTIFUL, UTAH 84010

(801) 298-1368 (PHONE)

(801) 298-2192 (FAX)

E-MAIL:

spevans@qwest.net


www.spe-architect.com


CONSULTANTS STRUCTURAL ENGINEER

BHB CONSULTING MECHANICAL ENGINEER VAN BOERUM & FRANK ASSOCIATES ELECTRICAL ENGINEER KEY ENGINEERING, INC.


A COPYRIGHT: SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE SCHEDULES






SCOTT P. EVANS ARCHITECT & ASSOCIATES P.C



108 WEST CENTER STREE

(801) 298-1368 (PHONE) (801) 298-2192 (FAX)



VAN BOERUM & FRANK ASSOCIATES


3/28/05 CONSTRUCTION DOCUMEN MARK DATE DESCRIPTION


WNER PROJECT NO: 05017150


COTT P. EVANS ARCHITECT - 2005


FLOOR PLANS & **KEYED NOTES**


AE-101
















ROOM FINISH SCHEDULE


					WALLS										
	ROOM	FLOOR	BASE	NO	RTH	EA	ST	SO	UTH	W	EST		CEILING		REMARKS
NUMBEF	NAME			MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	HEIGHT	
101	Attny./Client Conf.	Carpet	Rubber	Gyp. Bd.	Paint	Gyp. Bd.	Paint	Gyp. Bd.	Paint	Gyp. Bd.	Paint	2x2 Susp. Panel	None		
102	Conference Room	Carpet	Rubber	Gyp. Bd.	Paint	Gyp. Bd.	Paint	Gyp. Bd.	Paint	Gyp. Bd.	Paint	2x2 Susp. Panel	None		
103	Judge's Chambers	Carpet	Wood	Gyp. Bd.	V.W.C.	Gyp. Bd.	V.W.C.	Gyp. Bd.	V.W.C.	Gyp. Bd.	V.W.C.	2x2 Susp. Panel	None		
)4	Abstract Room					"No New F	inishes"							F	Patch/Paint if needed.
)5	Courtroom	New Carpet	*Extg. Base*	Hardwood Paneling	Transparent Finish	Extg. Gyp. Bd.	Extg. V.W.C.	Extg. Gyp. Bd.	Extg. V.W.C.	Extg. Gyp. Bd.	Extg. V.W.C.	2x2 Susp. Panel/Gyp. Bd.	None/Paint	Varies/10'-0" *	Patch & repair walls & base as required*
6	Jury Room	Extg. Carpet	Extg. Base	Extg. Gyp. Bd.	New Paint	Extg. Gyp. Bd.	New Paint	Extg. Gyp. Bd.	New Paint	Extg. Gyp. Bd.	New Paint	Extg.	Extg.		
07	Courtroom	Extg. Carpet/Patch	Extg. Base/Patch	Extg.	Extg.	Extg.	Extg.	Extg./Patch	Extg./V.W.C.	Extg.	Extg.	Extg.	Extg.		

DOOR	-RAMES
GLAZE WITH FLOAT GLA	SCALE 1/4" = 1'-0" 0 2' 4' 8' H 1/4" = 2"
2" 3'-0" 2"	SS 2" 3'-0"
HOLLOW METAL FRAME DOOR (PAINTED)	HOLLOW METAL FRAME DOOR (PAINTED)
"A"	"B"





3OUNTIFUL, UTAH 84010
(801) 298-1368 (PHONE)
(801) 298-2192 (FAX)
E-MAIL:
spevans@qwest.net
WEB:
www.spe-architect.com



CONSULTANTS

STRUCTURAL ENGINEER
BHB CONSULTING
MECHANICAL ENGINEER
VAN BOERUM & FRANK ASSOCIATES
ELECTRICAL ENGINEER
KEY ENGINEERING, INC.

CEDAR CITY COURT 2005 MISCELLANEOUS REMODELING

3/28/05 CONSTRUCTION DOCUMENT
MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150

ARCH. PROJECT NO: 04-47

CAD DWG FILE: AE-601.DWG

DRAWN BY: JBE


CHECKED BY: SPE

DESIGNED BY: SPE

COPYRIGHT:
SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE
SCHEDULES

AE-601



LEGEND OF MECHANICAL SYMBOLS AND ABBREVIATIONS

SINGLE LINE	DOUBLE LINE	<u></u>
SINGLE LINE	DOUBLE LINE	POSITIVE PRESSURE DUCT - RISE
		POSITIVE PRESSURE DUCT - DROP
		NEGATIVE PRESSURE DUCT - RISE
		NEGATIVE PRESSURE DUCT - DROP
	7	
		ROUND DUCT - RISE
	8 5	ROUND DUCT - DROP
	8 8	UNDER FLOOR DUCT
		TURNING VANES
	†	FRESH AIR LOUVER
	→	RELIEF AIR OR EXHAUST AIR LOUVER
─ ⊠	12X12 200	CEILING SUPPLY DIFFUSER
———————————————————————————————————————	200220	CEILING RETURN REGISTER
—	12X12 200	CEILING EXHAUST REGISTER, (BALANCE TO MATCH SUPPLY IF RETURN CFM IS NOT SHOWN)
———	_24X10 200	TOP FIGURES INDICATE SIDEWALL SUPPLY REGISTER NECK SIZE. BOTTOM FIGURE INDICATES CFM.
———	24X10, 200	SIDEWALL EXHAUST OR RETURN REGISTER
~~~\ <u>\</u>	12X12 200	CEILING SUPPLY DIFFUSER WITH FLEXIBLE DUCT
	24/24	CEILING RETURN AIR GRILE W/ SDUND BOOT
	3-1' SLOTS @ 48' 400	LINEAR DIFFUSER WITH PLENUM AND FLEXIBLE DUCT CONNECTION. NO. OF SLOTS ON TOP, ACTIVE LENGTH AND CFM ON BOTTOM
	<b></b>	FLEXIBLE DUCT CONNECTION
**********	<b>†</b>	FLEXIBLE DUCT
		FAN
12/8 FD	12/8 FD	FLAT DVAL DUCT WITH NET INSIDE DIMENSIONS SHOWN IN INCHES.
12/8	12/8	RECTANGULAR DUCT WITH NET INSIDE DIMENSIONS SHOWN IN INCHES.
12 <b>*</b> ø	\[ 12"\phi \]	ROUND DUCT WITH NET INSIDE DIMENSIONS SHOWN IN INCHES.
		INCLINED RISE WITH RESPECT TO AIR FLOW 15° NOMINAL INCLINE WITH
<u></u>	DN	INCLINED DROP RADIUS TURNS=DEPTH OF DUCT.
	W R	R/W=1. ROUND DUCT SIMILAR TO RECTANGULAR
15/15 8/8	12/12 78/8	RECTANGULAR TO RECTANGULAR OR ROUND TO ROUND DUCT TRANSFORMATION MAXIMUM 15° INCLUDED ANGLE EXCEPT WHERE SHOWN OTHERWISE.
9/9 > 9*ø	9/9 9'0	RECTANGULAR TO ROUND DUCT TRANSFORMATION
6	R	BRANCH DUCT SPLIT WITH 6' WIDTH AND MIN. R=WIDTH OF BRANCH DUCT DOWNSTREAM. ELBOW TURNING VANE OPTIONAL.
RECT. TO #	45° D D D	TAP ENTRY AREA EQUALS 150% OF BRANCH AREA
<del></del>	<del></del>	HIGH EFFICIENCY FITTING
<del></del>	+ +	MANUAL VOLUME DAMPER
FD	FD + -	FIRE DAMPER IN DUCT, W/ ACCESS PANEL REQD.
FSD	FSD	COMBINATION FIRE/SMOKE DAMPER W/ ACCESS PANEL
	SD	SMUKE DAMPER W/ ACCESS PANEL
OR PATC	ATCD OR	ATC DAMPER
AD	AD	ACCESS PANEL IN DUCT OR PLENUM
		HEATING OR COOLING COIL IN DUCT
~~~~ <u>////</u>		SINGLE DUCT AIR TERMINAL BOX VARIABLE OR CONSTANT VOLUME, MIN. 1-1/2 TERMINAL INLET SIZE STRAIGHT DUCT AT TERMINAL INLET.


<u>-GEND OF</u>	MECHANICAL SYMB
	4-WAY BLOW PATTERN
	3-WAY BLOW PATTERN
	2-WAY BLOW PATTERN
	2-WAY BLOW PATTERN
	1-WAY BLOW PATTERN
LPC	LOW PRESSURE CONDENSATE
MPC	MEDIUM PRESSURE CONDENSATE
——————————————————————————————————————	HIGH PRESSURE CONDENSATE
——— LPS ———	LOW PRESSURE STEAM
MPS	MEDIUM PRESSURE STEAM
——————————————————————————————————————	- HIGH PRESSURE STEAM
——————————————————————————————————————	BOILER BLOW DOWN
——————————————————————————————————————	BOILER FEED WATER
v	VACUUM
-000	PUMPED CONDENSATE
MUW	MAKE UP WATER
—— G ——	NATURAL GAS
(E)name	EXISTING PIPING
CHWS	
CHWR	
cs	OFFINE NATED OUDDLY
—— CR ——	CONDENSER WATER RETURN
——— HWS ———	
GHR	
G(NAME)	GLYCOL PIPING SOLUTION
——————————————————————————————————————	
-× × (NAME) -× ×	- EXISTING PIPING TO BE REMOVED
RL	- REFRIGERANT LIQUID
RS	- REFRIGERANT SUCTION
——— НG ————	- HOT GAS
FDS	- FUEL DIL SUPPLY
FDR	- FUEL DIL RETURN
———HFS———	- HELICOPTER FUEL SUPPLY
HFR	- HELICOPTER FUEL RETURN
CF	- CHEMICAL FEED
[S]	SOLENDID VALVE
-	EXPANSION JOINT
	ALIGNMENT GUIDE
-X X X	DEMOLITION
X	AHCHOR
<u> </u>	PRESSURE GAUGE WITH SHUT-OFF COCK
Q	PRESSURE GAUGE WITH PIGTAIL
	FLANGE

FLANGE

—- ⊢—	UNION
GPM LB/HR.	FLOW METER ORIFICE
<u> </u>	AIR VENT-MANUAL
	AIR VENT-AUTO
<u> </u>	FLOW SWITCH
— 	TEMPERATURE AND PRESSURE TEST PORT
<u> </u>	PRESSURE SWITCH
[RPBP]	REDUCED PRESSURE BACKFLOW PREVENTOR W/ DRAIN PAN
— —	PRESSURE REDUCING, SELF CONTAINED VALVE
- 	PRESSURE REDUCING, EXTERNAL PRESSURE VALVE
	BALL VALVE (PIPE SIZES 2" AND SMALLER) BUTTERFLY VALVE (PIPE SIZES 2-1/2" AND LARGER)
- -	CHECK VALVE
	MOTOR OPERATED BUTTERFLY VALVE
—-	GAS COCK
₩	RELIEF VALVE
- >>-	GATE VALVE
-121-	ATC VALVE - 2 WAY
C C	ATC VALVE - 3 WAY
- 	GLOBE VALVE
	FLOW CONTROL VALVE
	CALIBRATED BALANCING VALVE
——————————————————————————————————————	SHUT-OFF COCK FOR USE WITH PRESSURE GAUGE
	PUMP
	FLEXIBLE CONNECTION
	FLOW METER
	90° ELBOW
	45° ELBOW
	REDUCER
→>	CONCENTRIC REDUCER
	ECCENTRIC REDUCER
₽	LATERAL STRAINER WITH BLOW-OFF VALVE, PROVIDE HOSE END WITH CAP WHERE DISCHARGE IS NOT PIPED TO
	DRAIN THERM□METER 0-100°F
T	THERMOSTAT
⊕N	NIGHT THERMOSTAT
(\$)	SENSOR
F&T	STEAM TRAP, F&T=FLOAT & THERMOSTATIC B=BUCKET, T=THERMOSTATIC
<u>SD</u>	DUCT SMOKE DETECTOR
-	ARROW INDICATES DIRECTION OF FLOW IN PIPE
<u>DN</u>	LEADER INDICATES DOWNWARD SLOPE
G	PIPE INTO PLANE
0	PIPE OUT OF PLANE
ı	PIPE BRANCH - IN TO PLANE

PIPE BRANCH - OUT OF PLANE

PIPE BRANCH - IN PLANE



SCOTT P. EVANS
ARCHITECT
& ASSOCIATES P.C.



108 WEST CENTER STREET BOUNTIFUL, UTAH 84010 (801) 298-1368 (PHONE) (801) 298-2192 (FAX) E-MAIL: spevans@qwest.net

www.spe-architect.com

PROFESSIONAL SEAL

CONSULTANTS

STRUCTURAL ENGINEER
BHB CONSULTING

BHB CONSULTING

MECHANICAL ENGINEER

VAN BOERUM & FRANK ASSOCIATES

ELECTRICAL ENGINEER

KEY ENGINEERING, INC.

CEDAR CITY COURT
2005 MISCELLANEOUS
REMODELING
100 EAST CENTER STREET
CEDAR CITY, UTAH 84501

	03/28/05	CONSTRUCTION DOC.
MARK	DATE	DESCRIPTION
/		

OWNER PROJECT NO: 05017150

ARCH. PROJECT NO: 04-47

CAD DWG FILE: 4071_ME-000.DWG

DRAWN BY: Miah


CHECKED BY: BWR

DESIGNED BY: BWR

A COPYRIGHT:
SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE LEGEND

ME-000



MARK DATE DESCRIPTION

ARCHITECT

(801) 298-1368 (PHONE) (801) 298-2192 (FAX)

E-MAIL: spevans@qwest.net

www.spe-architect.com

PROFESSIONAL SEAL


CONSULTANTS

OWNER PROJECT NO: 05017150 DRAWN BY: Miah CHECKED BY: BWR DESIGNED BY: BWR

COPYRIGHT: SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE MECHANICAL **DEMOLITION PLANS**

MD-101



SCOTT P. EVANS
ARCHITECT

& ASSOCIATES P.C

108 WEST CENTER STREET BOUNTIFUL, UTAH 84010 (801) 298-1368 (PHONE) (801) 298-2192 (FAX) E-MAIL: spevans@qwest.net

www.spe-architect.com

PROFESSIONAL SEAL

CONSULTANTS

STRUCTURAL ENGINEER
BHB CONSULTING

MECHANICAL ENGINEER
VAN BOERUM & FRANK ASSOCIATES

ELECTRICAL ENGINEER
KEY ENGINEERING, INC.

CEDAR CITY COURT
2005 MISCELLANEOUS
REMODELING
100 EAST CENTER STREET
CEDAR CITY, UTAH 84501

03/28/05 CONSTRUCTION DOC.

MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150

ARCH. PROJECT NO: 04-47

CAD DWG FILE: 4071_ME-101.DWG

DRAWN BY: Miah


CHECKED BY: BWR

DESIGNED BY: BWR


COPYRIGHT:
SCOTT P. EVANS ARCHITECT - 2005

SHEET TITLE
MECHANICAL PLANS


ME-101 18 OF 26




W:\4000\40Z1 Ccdcr City Counts\40Z1 ME 401 dus 3/31/2006 12:00:06 BM Pc





M:\4000\4071 Cedar City Courts\4071_PD-101.dwg, 3/31/2005 12:08:55 PM, Dc





SYMBOL	MANUFACTURER	CATALOG NUMBER	LAMPS	DESCRIPTION
T-1	COLUMBIA	P4D 24-332-G-LD38-SEB8-120-GLR 2EP3GX-332-S-38I-120-EB82		2X4 3-LAMP, 24 CELL, LAY-IN PARABOLIC TROFFER, 3" DEEP CELLS FACTORY WRED FOR 2 LEVEL CENTER LAMP SWITCHING. 120 VOLT LOW HARMONIC ELECTRONIC BALLASTS, FUSED, LOW IRIDESCENT, SEMI-SPECULAR FINISH.
T-2	-	-	3) F32 T8/ SPX35 86 CRI LAMPS	EXISTING FIXTURE RELOCATED TO THIS NEW LOCATION 2X4 3—LAMP, PARABOLIC TROFFER — WITH 120 VOLT LOW HARMONIC ELECTRONIC DIMMING BALLASTS. 0 — 100% RANGE. FUSED, LOW IRIDESCENT SEMI—SPECULAR FINISH.
T-3	COLUMBIA	P422-232U6-G-LD35-SEB8-120-GLR 2EP3GX-2U6T8-S-34I-120-EB81	SPX35	2X2 2U LAMP 12 CELL LAY-IN PARABOLIC TROFFER 3" DEEP CELLS. 120 VOLT LOW HARMONIC ELECTRONIC BALLAST, FUSED, LOW IRIDESCENT SEMI-SPECULAR FINISH.
T-4	ALS	CL22-APPROX26.5-X120-E-0	12) F28 T5/ SPX35 86 CRI LAMPS	SURFACE ON WALL OF SKYLIGHT SHINING UPWARD — SEE ARCHITECTURAL DETAILS FOR MOUNTING — PROVIDE ENDS FOR MOUNTING THE ENTIRE LENGTH OF SKYLIGHT. MAKE FIELD MEASUREMENTS FOR ORDERING.
T-5	PORTFOLIO	PD7-V142-7VC	1) F32 TT SPX35 86 CRI LAMP	RECESSED DOWN LIGHT
T-6	PORTFOLIO	PD7-V120-7VP38-CL	1) 150W PAR 38 FLOOD LAMP	RECESSED DOWN LIGHT
T-7	HALO	L973P/L1510P	1) 50W PAR 20 FLOOD	SURFACE ON WALL OF SKYLIGHT — MOUNT ABOVE TRUSS AREA — SPOTLIGHTING DOWNWARD — ADJUSTIBLE
EX-1	PRESCOLITE SURE-LITES	XD-1-G-EN-W CX-7170-GW	INCL'D.	SINGLE FACE, UNIVERSAL MOUNT, CAST WHITE HOUSING, EXIT FIXTURE. GREEN LED, NI CAD EMERGENCY BATTERY.
_===				
ЕМ	PRESCOLITE IOTA BODINE	EFP-5 I-80 B-50		NEW FIELD INSTALLED 1100 LUMEN NI-CAD EMERGENCY BATTERY-PACK - 5 YEAR WARRANTED. NOTE: IF THERE IS CAPACITY IN THE EXISTING BUILDING CENTRAL BATTERY SYSTEM, DELETE INDIVIDUAL PUCKS + CONNECT ALL EM LIGHTS CENTRAL SYSTEM.





CEILING LIGHT IN GRID DETAIL

NO SCALE

EI-101

ARCHITECT
& ASSOCIATES P.C.

108 WEST CENTER STREET
BOUNTIFUL, UTAH 84010

(801) 298-1368 (PHONE)
(801) 298-2192 (FAX)

SCOTT P. EVANS



E-MAIL: spevans@qwest.net

STRUCTURAL ENGINEER
BHB CONSULTING
MECHANICAL ENGINEER

BHB CONSULTING

MECHANICAL ENGINEER

VAN BOERUM & FRANK ASSOCIATES

ELECTRICAL ENGINEER

KEY ENGINEERING, INC.

CEDAR CITY COURT
2005 MISCELLANEOUS
REMODELING
100 EAST CENTER STREET
CEDAR CITY, UTAH 84501

MARK DATE DESCRIPTION

OWNER PROJECT NO: 05017150

ARCH. PROJECT NO: 04-47

CAD DWG FILE: EI-101.DWG

DRAWN BY: MDL

CHECKED BY: DPL

DESIGNED BY: DPL


A COPYRIGHT:
SCOTT P. EVANS ARCHITECT - 2005


SHEET TITLE


ELECTRICAL

SCHEDULES &

DETAILS







108 WEST CENTER STREET BOUNTIFUL, UTAH 84010

(801) 298-2192 (FAX) spevans@qwest.net



